



## ARROW® RIGHT HEART PRODUCTS

Designed to meet clinician preference and patient needs



# THERMODILUTION CATHETER SERIES

## THREE DIFFERENT CATHETER BODY

### FIRMNESS LEVELS

- Insertion made easy with catheters from firm to soft
- Flow directed for easy positioning
- Torque controlled catheters for better maneuverability and control even at femoral insertion site; retains firmness *in situ* for a longer time
  - (T) Torque (control)
  - (FL) Flexi torque catheters slightly softer than torque (control)
  - (F) Flotation (softest)

## MULTIPLE OPTIONS

- Variety of French sizes from 4 Fr. to 7.5 Fr.
- Optional 4 or 5 lumen
- Optional polyurethane version reduces risks associated with PVC materials
- Available with or without Heparin coating

## CATHETER DESIGNED FOR EASY INSERTION, HANDLING AND MANAGEMENT

- Taper tip for easy handling while inserting through sheath
- No step-up at balloon/catheter junction
  - Allows equal sheath/catheter sizing if desired (7 Fr. catheter through 7 Fr. sheath)
  - Minimizes potential for vessel trauma and blood loss
- Larger distal lumen due to tapered tip design for better waveform visualization
- Simplified lumen identification with standard color-coding
- Translucent polyurethane extension lines
  - Allows easy identification of air bubbles



## THERMODILUTION CATHETERS

## CONVENTIONAL STYLE CATHETERS

PRODUCT NO.	FRENCH SIZE	HEPARIN COATED	USEFUL LENGTH	NO. OF LUMENS	CATHETER BODY STYLE	RECOM'D INTRODUCER SIZE	BALLOON MAXIMUM CAPACITY	BALLOON INFLATED DIAMETER	MAXIMUM WIRE FOR INSERTION	CVP PROXIMAL LUMEN PORT DISTANCE FROM TIP	INFUSION LUMEN PORT DISTANCE FROM TIP	CE MARK
AI-07044	4 Fr.	No	75 cm	4	T	5 Fr.	.75 cc	8 mm	0.014 in	10 cm	n/a	Yes
AI-07044-H	4 Fr.	Yes	75 cm	4	T	5 Fr.	.75 cc	8 mm	0.014 in	10 cm	n/a	No
AI-07055-H	5 Fr.	Yes	80 cm	4	T	5 or 6 Fr.	1.0 cc	8 mm	0.018 in	10 cm	n/a	No
AI-07065	5 Fr.	Yes	80 cm	4	T	5 or 6 Fr.	1.0 cc	8 mm	0.018 in	15 cm	n/a	No
AI-07165	5 Fr.	No	80 cm	4	T	5 or 6 Fr.	1.0 cc	8 mm	0.018 in	15 cm	n/a	Yes
AI-07365-H	6 Fr.	Yes	80 cm	4	T	6 or 7 Fr.	1.0 cc	10 mm	0.018 in	15 cm	n/a	No
AI-07365-HL	6 Fr.	Yes	110 cm	4	T	6 or 7 Fr.	1.0 cc	10 mm	0.018 in	15 cm	n/a	No
AI-07067	7 Fr.	Yes	110 cm	4	T	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	No
AI-07167	7 Fr.	No	110 cm	4	T	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	Yes
AI-07367	7 Fr.	No	110 cm	4	F	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	Yes
AI-07368	7 Fr.	Yes	110 cm	4	F	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	No
AI-07368-F	7 Fr.	Yes	110 cm	4	FL	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	No
AI-07368-NHF	7 Fr.	No	110 cm	4	F	7 or 8 Fr.	1.5 cc	12 mm	0.025 in	29 cm	n/a	No

## CATHETERS WITH INFUSION PORT

AI-07077	7.5 Fr.	Yes	110 cm	5	T	8.5 Fr.	1.5 cc	12 mm	0.025 in	29 cm	31 cm	No
AI-07077-G	7.5 Fr.	No	110 cm	5	FL	8.5 Fr.	1.5 cc	12 mm	0.025 in	29 cm	31 cm	Yes
AI-07377	7.5 Fr.	Yes	110 cm	5	F	8.5 Fr.	1.5 cc	12 mm	0.025 in	29 cm	31 cm	No
AI-07377-NH	7.5 Fr.	No	110 cm	5	F	8.5 Fr.	1.5 cc	12 mm	0.025 in	29 cm	31 cm	No

## HANDS-OFF® THERMODILUTION CATHETERS WITH TWISTLOCK™ CATH-GARD® CATHETER CONTAMINATION SHIELD AND INTEGRAL BALLOON FLUSHING/TEST CHAMBER

## CONVENTIONAL STYLE CATHETERS

PRODUCT NO.	FRENCH SIZE	HEPARIN COATED	USEABLE LENGTH	NO. OF LUMENS	CATHETER BODY STYLE	RECOM'D INTRODUCER SIZE	BALLOON MAXIMUM CAPACITY	BALLOON INFLATED DIAMETER	MAXIMUM WIRE FOR INSERTION	CVP PROXIMAL LUMEN PORT DISTANCE FROM TIP	INFUSION LUMEN PORT DISTANCE FROM TIP	CE MARK	ADDITIONAL KIT CONTENTS CATH-GARD
AH-05000	7 Fr.	No	110 cm	4	F	8 Fr.	1.5 cc	12 mm	0.030 in	29 cm	n/a	Yes	7.0 Fr. x 112 cm
AH-05000-F	7 Fr.	No	110 cm	4	F	8 Fr.	1.5 cc	12 mm	0.030 in	29 cm	n/a	Yes	7.0 Fr. x 112 cm
AH-05000-H	7 Fr.	Yes	110 cm	4	F	8 Fr.	1.5 cc	12 mm	0.030 in	29 cm	n/a	No	7.0 Fr. x 112 cm
AH-05050	7.5 Fr.	No	110 cm	5	T	8.5 Fr.	1.5 cc	12 mm	0.030 in	29 cm	31 cm	Yes	7.5 Fr. x 112 cm
AH-05050-D	7.5 Fr.	No	110 cm	5	F	8.5 Fr.	1.5 cc	12 mm	0.030 in	29 cm	31 cm	Yes	7.5 Fr. x 112 cm
AH-05050-G	7.5 Fr.	No	110 cm	5	FL	8.5 Fr.	1.5 cc	12 mm	0.030 in	29 cm	31 cm	Yes	7.5 Fr. x 112 cm
AH-05050-H	7.5 Fr.	Yes	110 cm	5	T	8.5 Fr.	1.5 cc	12 mm	0.030 in	29 cm	31 cm	No	7.5 Fr. x 112 cm
AH-05050-PU	7.5 Fr.	No	110 cm	5	T	8.5 Fr.	1.5 cc	12 mm	0.030 in	29 cm	31 cm	Yes	7.5 Fr. x 112 cm

NOTE: Catheter body style: T – Higher Torque Control FL – Flexi Torque (mid-range) F – Flotation (softest)  
Each package includes: Thermistor catheter, Control stroke syringe, non-vented dust cap, extension line clamps